

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)


PCT

(10) International Publication Number
WO 2005/096420 A2

- (51) International Patent Classification⁷: **H01M 8/00**
- (21) International Application Number: PCT/JP2005/006546
- (22) International Filing Date: 28 March 2005 (28.03.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2004-109018 1 April 2004 (01.04.2004) JP
2004-177649 15 June 2004 (15.06.2004) JP
- (71) Applicant (for all designated States except US): **YAMAHA HATSUDOKI KABUSHIKI KAISHA** [JP/JP]; 2500, Shingai, Iwata-shi, Shizuoka 438-8501 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **MURAMATSU, Yasuyuki** [JP/JP]; c/o Yamaha Hatsudoki Kabushiki, Kaisha, 2500 Shingai, Iwata-shi, Shizuoka 438-8501 (JP). **OISHI, Masatsugu** [JP/JP]; c/o Yamaha Hatsudoki
- (74) Agent: **TATSUMI, Tadahiro**; 8th floor, Ueroku Shinkosan Bldg., 2-11, Uehommachi 5-chome, Tennoji-ku, Osaka-shi, Osaka 543-0001 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: FUEL CELL SYSTEM AND CONTROL METHOD THEREFOR



(57) Abstract: A fuel cell system that has a simple construction and is capable of preventing fluid from being discharged outside, and a control method therefor, are provided. A fuel cell system 10 preferably includes a fuel cell 12 which generates electric energy by electro-chemical reaction, an aqueous solution tank 18 which holds the methanol aqueous solution S, a water tank 44 which holds fluid discharged from the fuel cell 12, a fluid level sensor 54 for detecting an amount of fluid in the water tank 44, a water pump 60 which recycles fluid in the water tank 44 to the aqueous solution tank 18, and a CPU 72 which controls components of the fuel cell system 10. After power generation is finished, the water pump 60 is driven to recycle all the fluid in the water tank 44 to the aqueous solution tank 18. Further, after power generation is finished or before power generation is started, the fluid level sensor 54 detects the amount of in the water tank 44. If the amount of fluid is not smaller than a predetermined amount, the water pump 60 is driven to recycle fluid in the water tank 44 to the aqueous solution tank 18.

WO 2005/096420 A2



Published:

- without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.